NSN 4720-00-580-9071

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-580-9071

Inside Diameter:						
0.375 inches						
Outside Diameter:						
0.812 inches						
Minimum Inside Bending Radius:						
4.000 inches						
Inner Conveying Tube Style:						
Helical close-pitch corrugated						
Exterior Color:						
Natural						
Connection Style:						
Swivel nut flare 1st end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Features Provided:						
Identical ends						
Burst Test Pressure:						
6000.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided corrosion resistant steel wire						
Maximum Operating Pressure:						
1500.0 pounds per square inch						
Thread Size:						
0.562 inches 1st end						
Seat Angle:						
37.5 degrees 1st end						
•						
37.5 degrees 1st end						
37.5 degrees 1st end Hydrostatic Test Pressure:						
37.5 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch						
37.5 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection:						
37.5 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant						
37.5 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Measuring Method And Length:						
37.5 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Measuring Method And Length: 15.375 inches						

NSN 4720-00-580-9071

Metallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0