NSN 4720-00-583-5236

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-583-5236

Cross Sectional Shape:
Round
Thread Class:
3b 2nd end
Thread Direction:
Right-hand 2nd end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 131.0 degrees fahrenheit single response
Outside Diameter:
0.400 inches
Minimum Inside Bending Radius:
2.500 inches
Inner Conveying Tube Style:
Helical open-pitch corrugated
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 2nd end
Burst Test Pressure:
150.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
50.0 pounds per square inch
Thread Size:
0.438 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
100.0 pounds per square inch
Flow Angle:
96.0 degrees 2nd end
Measuring Method And Length:
7.730 inches working
Thread Series Designator:
Unjf 2nd end
Shelf Life:
N/a

NSN 4720-00-583-5236

Metallic Hose Assembly - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A542a0