Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-585-0282

| Cross Section | onal Shape: |
|----------------|---|
| Round | |
| Thread Clas | s: |
| 3b 1st end | |
| Thread Dire | ction: |
| Right-hand 1 | st end |
| Inside Diam | eter: |
| 0.188 inches | |
| Tempurature | e Rating: |
| -65.0 degree | s fahrenheit single response and 160.0 degrees fahrenheit single response |
| Outside Dia | meter: |
| 0.516 inches | |
| Minimum Ins | side Bending Radius: |
| 2.000 inches | |
| Connection | Style: |
| Swivel nut fla | are 2nd end |
| End Connec | tion Design: |
| Straight 1st e | and |
| Connection | Туре: |
| Threaded inte | ernal tube 1st end |
| Burst Test P | Pressure: |
| 12000.0 pour | nds per square inch |
| Layer Comp | osition And Location: |
| Outer layer b | raided corrosion resistant steel wire |
| Maximum O | perating Pressure: |
| 3000.0 pound | ds per square inch |
| Thread Size: | : |
| 0.438 inches | 1st end |
| Seat Angle: | |
| 37.0 degrees | s 1st end |
| Hydrostatic | Test Pressure: |
| 6000.0 pound | ds per square inch |
| Flow Angle: | |
| 90.0 degrees | 2nd end |
| Outer Cover | ing Environmental Protection: |
| Corrosion res | sistant |
| Vacuum In T | Forr: |
| 50.8 | |
| Inside Surfa | ce Condition: |
| Smooth | |
| Measuring N | lethod And Length: |
| 5.000 inches | working |
| | |



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0