

View Online at <https://aerobasegroup.com/nsn/4720-00-585-0513>

Cross Sectional Shape:

Round

Inside Diameter:

2.438 inches

Width Across Flats:

4.000 inches 2nd end

Bolt Circle Diameter:

3.812 inches 2nd end

Flange Thickness:

0.313 inches 2nd end

Outside Diameter:

2.750 inches

Bolt Hole Quantity:

6 2nd end

Flange Length:

3.810 inches 2nd end

Connection Style:

Raised swivel 2nd end

Bolt Hole Diameter:

0.281 inches 2nd end

Raised Face Height:

0.031 inches 2nd end

Raised Face Diameter:

3.281 inches 2nd end

End Flange Construction:

Split 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Raised face flange 2nd end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

560.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

120.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

31.000 inches

Flange Style:

Hexagon 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0