NSN 4720-00-585-0666

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-585-0666

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Outside Diameter:
0.516 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated cotton fabric
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Mildew resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
93.000 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Specification Data:
96906-ms28741 government specification
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-00-585-0666

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0