NSN 4720-00-585-2289

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-585-2289

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
221.0 degrees fahrenheit single response
End Application:
Grumman a10 aircraft
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal hose 1st end
Thready Qty Per Inch (tpi):
11-1/2 2nd end
Burst Test Pressure:
600.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer spirally wrapped fabric and 3rd layer spirally wrapped fabric and 4th layer woven fabric and 5th
layer woven fabric and outer layer molded rubber, synthetic
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Outer Covering Environmental Protection:
Ozone resistant and weatherproof
Measuring Method And Length:
600.000 inches excluding end fittings
Media For Which Designed:
Water, fresh single response
Thread Series Designator:
Nh 2nd end
Specification Data:
81348-zz-h-601 government specification
Specification Or Standard:
1 grade and 1 class

N/a

Shelf Life:

NSN 4720-00-585-2289

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0