## NSN 4720-00-586-3666

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-586-3666

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
800.0 pounds per square inch
Layer Composition And Location:
1st layer woven cotton with interwoven steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Grease resistant and oil resistant and water resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.250 inches
Media For Which Designed:

wedia For Willen Designe

Hydraulic fluid single response

## NSN 4720-00-586-3666

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator	tor:
--------------------------	------

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0