Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-586-4654

Cross Sectional	Shape:
Round	
Thread Class:	
2b 1st end	
Thread Direction	
Right-hand 1st end	i
Inside Diameter:	
0.625 inches	
Tempurature Rat	ng:
-40.0 degrees fahi	enheit and 275.0 degrees fahrenheit single response
Outside Diameter	:
1.078 inches	
Minimum Inside I	Bending Radius:
6.500 inches	
Connection Style	:
Swivel nut flare 1s	tend
End Connection	Design:
Straight 1st end	
Connection Type	
Threaded internal	tube 1st end
Thready Qty Per	nch (tpi):
12 1st end	
Burst Test Press	ıre:
6000.0 pounds pe	square inch
Layer Composition	on And Location:
1st layer braided o	otton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operat	ing Pressure:
1500.0 pounds pe	square inch
Thread Size:	
1.062 inches 1st e	nd
Seat Angle:	
37.0 degrees 1st e	nd
Vacuum In Torr:	
50.8	
Inside Surface Co	ondition:
Smooth	
Measuring Metho	d And Length:
21.156 inches wo	king
Media For Which	Designed:
	/drocarbon single response
Thread Series De	
Un 1st end	

NSN 4720-00-586-4654

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

