Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-586-4824

Cross Sectional Shap	be:
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
1.125 inches	
Tempurature Rating:	
-40.0 degrees fahrenh	eit and 275.0 degrees fahrenheit single response
Outside Diameter:	
1.500 inches	
Minimum Inside Ben	ding Radius:
9.000 inches	
Connection Style:	
Swivel nut flare 1st en	t
End Connection Des	gn:
Straight 1st end	
Connection Type:	
Threaded internal tube	a 1st end
Thready Qty Per Inch	(tpi):
12 1st end	
Burst Test Pressure:	
2500.0 pounds per squ	uare inch
Layer Composition A	nd Location:
1st layer braided cotto	n cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operating	Pressure:
625.0 pounds per squa	are inch
Thread Size:	
1.625 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Vacuum In Torr:	
254.0	
Inside Surface Condi	tion:
Smooth	
Measuring Method A	nd Length:
45.719 inches working	3
Media For Which Des	signed:
	carbon single response
Thread Series Design	
Un 1st end	

NSN 4720-00-586-4824

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0