## NSN 4720-00-586-5048

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-586-5048

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.812 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
2.219 inches
Minimum Inside Bending Radius:
13.250 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
1400.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
350.0 pounds per square inch
Thread Size:
2.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Vacuum In Torr:
482.6
Inside Surface Condition:
Smooth
Measuring Method And Length:
44.688 inches working
Media For Which Designed:
Air and fuel/oil, hydrocarbon single response
Thread Series Designator:

Un 1st end

## NSN 4720-00-586-5048

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0