Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-586-5200

Cr	oss Sectional Shape:
	und
Th	read Class:
	1st end
Th	read Direction:
	pht-hand 1st end
Ins	side Diameter:
Be	tween 0.172 inches and 0.203 inches
Ou	itside Diameter:
Be	tween 0.359 inches and 0.391 inches
Со	nnection Style:
Sw	rivel nut flare 1st end
En	d Connection Design:
Str	aight 2nd end
Co	nnection Type:
Th	readed internal tube 1st end
Bu	rst Test Pressure:
20	00.0 pounds per square inch
La	yer Composition And Location:
1st	layer braided cotton cord and outer layer molded rubber
Ма	iximum Operating Pressure:
50	0.0 pounds per square inch
Th	read Size:
0.4	38 inches 1st end
Se	at Angle:
45	0 degrees 1st end
Hy	drostatic Test Pressure:
10	00.0 pounds per square inch
Ou	ter Covering Environmental Protection:
Fu	el resistant and oil resistant and weatherproof
Va	cuum In Torr:
25	4.0
Ins	side Surface Condition:
Sm	nooth
Ме	easuring Method And Length:
10	.000 inches
Ме	dia For Which Designed:
Fu	el/oil, hydrocarbon single response
Th	read Series Designator:
Un	f 1st end
Sp	ecification Or Standard:
2 t	уре

NSN 4720-00-586-5200

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

