## NSN 4720-00-587-0568

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-587-0568 **Cross Sectional Shape:** Round **Inside Diameter:** 4.000 inches **Minimum Inside Bending Radius:** 12.000 inches **Exterior Color:** Black **Quick Disconnect Size:** 4.000 inches 2nd end **Connection Style:** Cam or lever (external) 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Internal quick disconnect 1st end **Features Provided:** Electrostatic discharge capability **Layer Composition And Location:** 1st layer braided steel wire and outer layer molded rubber **Maximum Operating Pressure:** 45.0 pounds per square inch **Hydrostatic Test Pressure:** 50.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and fuel resistant and hydraulic solution resistant and oil resistant and ozone resistant Vacuum In Torr: 381.0 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 20.800 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Test Data Document:** 01413-114289 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 4720-00-587-0568

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0