

View Online at <https://aerobasegroup.com/nsn/4720-00-587-6302>

Cross Sectional Shape:

Round

Inside Diameter:

1.125 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Bolt Circle Diameter:

3.120 inches 2nd end

Flange Thickness:

0.370 inches 2nd end

Outside Diameter:

1.500 inches

Minimum Inside Bending Radius:

9.000 inches

Angle Between Rigid Elbow Fittings In Deg:

115.0

Center To Center Distance Between Bolt Holes Along Width:

1.660 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.660 inches 1st end

Bolt Hole Quantity:

3 1st end

Flange Length:

3.120 inches 2nd end

Flange Width:

3.120 inches 2nd end

Connection Style:

Raised 2nd end

Bolt Hole Diameter:

0.266 inches 1st end

Raised Face Height:

0.009 inches 2nd end

Raised Face Diameter:

1.780 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Raised face flange 2nd end

Burst Test Pressure:

2500.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

500.0 pounds per square inch

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

49.500 inches working

Flange Style:

Triangular 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0