## NSN 4720-00-591-4388

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-591-4388 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.438 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.688 inches **Minimum Inside Bending Radius:** 5.750 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

**Hydrostatic Test Pressure:** 

6000.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Corrosion resistant

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

44.000 inches working

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

## NSN 4720-00-591-4388

Nonmetallic Hose Assembly - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A542a0