NSN 4720-00-591-8005

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-591-8005

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.312 inches |
| Tempurature Rating: |
| -40.0 degrees celsius and 85.0 degrees celsius single response |
| Outside Diameter: |
| 0.562 inches |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Complete fitting stainless steel all ends |
| Fitting Component And Surface Treatment: |
| Complete fitting passivate 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Second End Relationship With First End: |
| Identical |
| Burst Test Pressure: |
| 14000.0 pounds per square inch |
| First End Swivel Action Capability: |
| Not included |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.562 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 6000.0 pounds per square inch |
| Outer Covering Environmental Protection: |

Corrosion resistant and fuel resistant and oil resistant

NSN 4720-00-591-8005

A542a0

Nonmetallic Hose Assembly - Page 2 of 2



| Inside Surface Condition: | |
|--|--|
| Smooth | |
| Measuring Method And Length: | |
| 44.000 inches working | |
| Special Features: | |
| Inner conveying tube material-plastic, polytetrafluoroethylene; vinyl external support | |
| Thread Series Designator: | |
| Unjf 1st end | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiia· | |