NSN 4720-00-592-2412

Metallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-592-2412

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Outside Diameter:
1.094 inches
Inner Conveying Tube Style:
Helical close-pitch corrugated
Connection Style:
Flared 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
14 1st end
Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
Layer Composition And Location: Outer layer braided bronze wire
Outer layer braided bronze wire
Outer layer braided bronze wire Maximum Operating Pressure:
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size:
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size: 1.062 inches 1st end
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle:
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 45.0 degrees 2nd end
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 45.0 degrees 2nd end Measuring Method And Length:
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 45.0 degrees 2nd end Measuring Method And Length: 10.188 inches working
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 45.0 degrees 2nd end Measuring Method And Length: 10.188 inches working Thread Series Designator:
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 45.0 degrees 2nd end Measuring Method And Length: 10.188 inches working Thread Series Designator: Uns 1st end
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 45.0 degrees 2nd end Measuring Method And Length: 10.188 inches working Thread Series Designator: Uns 1st end Shelf Life:
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 45.0 degrees 2nd end Measuring Method And Length: 10.188 inches working Thread Series Designator: Uns 1st end Shelf Life: N/a
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 45.0 degrees 2nd end Measuring Method And Length: 10.188 inches working Thread Series Designator: Uns 1st end Shelf Life: N/a
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 45.0 degrees 2nd end Measuring Method And Length: 10.188 inches working Thread Series Designator: Uns 1st end Shelf Life: N/a Unit Of Measure:
Outer layer braided bronze wire Maximum Operating Pressure: 1400.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 45.0 degrees 2nd end Measuring Method And Length: 10.188 inches working Thread Series Designator: Uns 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: