NSN 4720-00-592-5265

Nptf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-592-5265

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.675 inches
Minimum Inside Bending Radius:
3.120 inches
Exterior Color:
Black
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
32.000 inches
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:

NSN 4720-00-592-5265

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0