

View Online at <https://aerobasegroup.com/nsn/4720-00-592-6630>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.438 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

**Outside Diameter:**

0.688 inches

**Minimum Inside Bending Radius:**

5.750 inches

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

14000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

34.000 inches working

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0