Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-592-6777

	nal Shape:
Round	
Thread Class	:
3b 1st end	
Thread Direc	tion:
Right-hand 1s	t end
Inside Diame	ter:
0.406 inches	
Tempurature	Rating:
-65.0 degrees	fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Dian	neter:
Between 0.54	6 inches and 0.585 inches
Minimum Ins	ide Bending Radius:
4.625 inches	
Connection S	Style:
Swivel nut flar	e 1st end
End Connect	ion Design:
Straight 1st er	nd
Connection 1	уре:
Threaded inte	rnal tube 1st end
Burst Test Pr	essure:
6000.0 pound	s per square inch
Layer Compo	osition And Location:
Outer layer br	aided corrosion resistant steel wire
Maximum Op	erating Pressure:
1500.0 pound	s per square inch
Thread Size:	
0.750 inches	lst end
Seat Angle:	
37.0 degrees	1st end
Hydrostatic 1	Test Pressure:
3000.0 pound	s per square inch
Inside Surfac	e Condition:
Smooth	
Measuring M	ethod And Length:
25.000 inches	working
Thread Serie	s Designator:
Unjf 1st end	
Shelf Life:	
N/a	
Unit Of Meas	ure:

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0