## NSN 4720-00-592-8935

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-592-8935

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.218 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.625 inches
Connection Style:
Swivel nut with loose or integral clinch sleeve 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
11.000 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Specification Data:
96906-ms28762 government standard
Shelf Life:

N/a

## NSN 4720-00-592-8935

Nonmetallic Hose Assembly - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A542a0