Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-592-8937

Bross occusion on procession of the process of the procession of t	Cross Sectional Shape:
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0:219 incles Tempurature Rating: 0:50. degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0:625 incles Connection Style: Connection Design: Straight 1st end Thread Quy Per Indep(it): 20 1st end Burst Test Pressure: 10000.0 pounds per square inch Layer Composition And Location: 112 Agerees Ist end Douts per square inch Layer Draided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maintone State Ist end Dout per square inch Layer Composition And Location: 12.0 degrees 1st end Matoreace Condition: 12.0 degrees 1st end Horden Condition: Diod Guendes per square inch	
3b 1st end Firead Direction: Right-hand 1st end Right-hand 1st end Databeer: 0.219 inches Tempurature Rating: -6.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.425 inches Connection Style: Solvel nut with loose or integral clinch sleeve 1st end End Connection Design: Straight 1st end Threaded Internal tube 1st end Threaded Internal tube 1st end Threade Jone Straight 1st end Straight 2st Pressure: 18000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloropreme Maximum Operating Pressure: 000.0 pounds per square inch Hydrostatic Test Pressure: 12.0 degrees 1st end Statal steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloropreme 000.0 pounds per square inch Statal steel 12.0 degrees 1st end Statal steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloropreme 12.0 degrees 1st end </th <th></th>	
Tread Direction: Right-hand 1st end Right-hand 1st end Inside Diameter: 0:219 inches Temprature Rating: 0:dotsgrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0:dotsgrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0:dotsgrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0:dotsgrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0:dotsgrees fahrenheit and 200.0 degrees fahrenheit single response Connection Design: Threaded internal tube of st end Threaded internal tube 1st end Threaded internal tube 1st end Threaded internal tube 1st end Burst Test Pressure: 1000.0 pounds per square inch Maximum Operating Pressure: 0:dot pounds per square inch State Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 0:dot pounds per square inch Ruder Strees Designator: 12.0 degrees 1st end Hydrostatic Test Pressure: 0:dot pounds per square inch<	
Right-hand 1st end Inside Diameter: 0.219 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Connection Style: Swivel nut with loose or integral clinch sleeve 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end Threaded internal tube 1st end Straight 2 response 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Stat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Stat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: <tr< td=""><td></td></tr<>	
Inside Diameter: 0.219 Inches 0.219 Inches Tempurature Rating: -85.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.625 Inches Connection Style: Swivel nut with loose or integral clinch sleeve 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 1000.0 pounds per square inch Exper Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 3000.0 pounds per square inch Exper Sat Angle: 31.0 degrees 1st end Hydrostati Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Seat Angle: 31.0 degrees 1st end Hydrostati Test Pressure: 3000.1 pounds per square inch Inside Surface Condition: Smooth Inter Sat Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Inter Sat Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Inter Sat Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Inter Sat Pressure: 3000.0 pounds per square inch Inter Sater Sate	
219 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Connection Style: Swivel nut with loces or integral clinch sleeve 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 000.0 pounds per square inch Thread Size: 0.438 inches 1st end Strates 1st end Materian Pressure: 0.438 inches 1st end Strate Condition: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smoth Thread Size: 0.1438 inchees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surf	-
Tempurature Rating: 0:60 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0:625 inches Connection Style: Swivel nut with loose or integral clinch sleeve 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Guy Per Inch (tpi): 20 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 0300.0 pounds per square inch Thread Size: 0.438 inches 1st end Stet Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 0300.0 pounds per square inch Inded Surface Condition: Stet Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 0300.0 pounds per square inch Inded Surface Condition: Stet Angle: 13.1 degrees 1st end Hydrostatic Test Pressure: N	
-b.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Connection Style: Swivel nut with loose or integral clinch sleeve 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Oty Per Inch (tpi): 20 1st end Burst Test Pressure: 18000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 300.0 pounds per square inch Lyca degrees 1st end Stet Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 13.0 degrees 1st end Inside Surface Condition: Steid Surface Condition: Inside Surface Condition: Inf lat end Shef Life: Inf 1st end	
Outside Diameter: 0.625 inches Connection Style: Swivel nut with loose or integral clinch sleeve 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Stat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: 13.0 degrees 1st end Hydrostatic Test Pressure: 10.0 dogrees 1st end Inside Surface Condition: Inside Surface Condition: Inside Surface Condition: Inside Surface Condition: Infield end Surface Insignator: Unf 1st end Shelf Life: I	
0.625 inches Connection Style: Swivel nut with loose or integral clinch sleeve 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Chready Qty Per Inch (tpi): 20 1st end Entert Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 1.2.0 degrees 1st end Hydrostatic Test Pressure: S000.0 pounds per square inch Seat Angle: 1.2.0 degrees 1st end Hydrostatic Test Pressure: S000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Uni 1st end Shelf Life: Na Mai Diff Measure: Na	
Connection Style: Swivel nut with loose or integral clinch sleeve 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st alver braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Yudrostatic Test Pressure: 8000.0 pounds per square inch Hydrostatic Test Pressure: 8000.0 pounds per square inch Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Interd Series Designator: Un fist end Shelf Life: N/a Shelf Life: N/a Dint Measure: Image: Image: Image: Image: Image: <	
Swivel nut with loose or integral clinch sleeve 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Side Surface Condition: Smooth Thread Series Designator: Unf 1st end Sheff Life: Na Chi Cheesure: Chi Chee	
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Sheff Life: N/a Unt Of Measure: Demilitarization:	
Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Sheff Life: N/a Uht Of Measure: The Composition: Thread Series Designator: Unit of Measure: Na During Test Pressure: Na During Test Pressure: Na During Test Pressure: During Test Pressure: During Test Pressure: Smooth Life: <t< td=""><td>-</td></t<>	-
Nonection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Un 1 st end Sheff Life: N/a Un 1 st end Sheff Life: N/a Unt Of Measure: - Penillitarization:	-
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Sheff Life: N/a Unit Of Measure: Demilitarization:	
Thready Qty Per Inch (tpi): 20 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Augeres 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Sheff Life: N/a Uni Of Measure: Demilitarization:	
20 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 0400.0 pounds per square inch Thread Size: 0.438 inches 1st end Steat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Sheff Life: N/a Unf 1st end Sheff Life: N/a	
Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Uni f0 Measure: Demilitarization:	
16000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:	
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Chread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: 	
Maximum Operating Pressure:3000.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:12.0 degrees 1st endHydrostatic Test Pressure:8000.0 pounds per square inchInside Surface Condition:SmoothThread Series Designator:Unf 1st endShelf Life:N/aUnit Of Measure:Demilitarization:	
3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:	
0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: 	
Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:	
12.0 degrees 1st end Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Hydrostatic Test Pressure: 8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:	-
8000.0 pounds per square inch Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Inside Surface Condition: Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Smooth Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Shelf Life: N/a Unit Of Measure: Demilitarization:	-
N/a Unit Of Measure: Demilitarization:	
Unit Of Measure: Demilitarization:	
 Demilitarization:	
Demilitarization:	

NSN 4720-00-592-8937

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

