

synthetic and outer layer rubber impregnated braided cotton cord

| Nonmetallic Hose Assembly - Page 1 of 1                                 |
|---|
| View Online at https://aerobasegroup.com/nsn/4720-00-592-9729           |
| Cross Sectional Shape:  |
| Round   |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.375 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response   |
| Outside Diameter:   |
| 0.781 inches  |
| Connection Style:   |
| Plain 1st end   |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded external pipe 1st end  |
| Thready Qty Per Inch (tpi):   |
| 18 1st end  |
| Layer Composition And Location:   |
| 1st layer braided steel wire and 2nd layer molded rubber, synthetic and |
| Maximum Operating Pressure:   |
| 2000.0 pounds per square inch   |
| Thread Size:  |
| 0.375 inches 1st end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 78.000 inches   |
| Media For Which Designed:   |
| Fuel/oil, hydrocarbon single response                                   |
| Thread Series Designator:   |
| Npt 1st end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A542a0  |
|   |
|   |
|   |