NSN 4720-00-593-3015

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-593-3015

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
10.700 inches working
Special Features:
Hose covered w/chafing guard
Thread Series Designator:
Unf 1st end

NSN 4720-00-593-3015

Nonmetallic Hose Assembly - Page 2 of 2



Sp	eci	ifi	cat	ior	า D	ata:
- [

07482-102a136+060106c manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0