NSN 4720-00-594-9410

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-594-9410

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.781 inches
Minimum Inside Bending Radius:
3.124 inches
Connection Style:
Swivel nut, inverted flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
5600.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided fabric and outer layer molded rubber, synthetic
Maximum Operating Pressure:
1300.0 pounds per square inch
Thread Size:
0.625 inches 1st end
Seat Angle:
45.0 degrees 2nd end
Hydrostatic Test Pressure:
2600.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
37.000 inches
37.000 inches Media For Which Designed:

Unf 2nd end

Thread Series Designator:

NSN 4720-00-594-9410

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0