Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-594-9836

С	ross Sectional Shape:
	ound
Т	hread Class:
3	b 1st end
Т	hread Direction:
R	ight-hand 1st end
Ir	side Diameter:
0	.188 inches
T	empurature Rating:
	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
	utside Diameter:
0	.312 inches
M	linimum Inside Bending Radius:
	.000 inches
С	onnection Style:
	wivel nut flare 2nd end
Е	nd Connection Design:
	traight 1st end
С	onnection Type:
Т	hreaded internal tube 1st end
F	eatures Provided:
Е	lectrostatic discharge capability
в	urst Test Pressure:
12	2000.0 pounds per square inch
Ŀ	ayer Composition And Location:
0	uter layer braided corrosion resistant steel wire
M	laximum Operating Pressure:
1!	500.0 pounds per square inch
Т	hread Size:
0	438 inches 1st end
s	eat Angle:
3	7.0 degrees 2nd end
н	ydrostatic Test Pressure:
3	000.0 pounds per square inch
F	low Angle:
30	0.0 degrees 2nd end
v	acuum In Torr:
5	0.8
In	side Surface Condition:
s	mooth
M	leasuring Method And Length:
18	8.000 inches working

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0