## NSN 4720-00-595-0168

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-595-0168

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.713 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided cotton cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
40.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Nptf 1st end
Shelf Life:
N/a
Unit Of Measure:

## NSN 4720-00-595-0168

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0