## NSN 4720-00-595-0590

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-595-0590 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.312 inches **Outside Diameter:** 0.672 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Outer Covering Environmental Protection:** Mildew resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 20.500 inches working **Thread Series Designator:** Unf 1st end **Specification Data:** 96906-ms28741 government standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 4720-00-595-0590

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0