Nonmetallic Hose Assembly - Page 1 of 2



chloroprene

View Online at https://aerobasegroup.com/nsn/4720-00-595-0989

| Cross Sectional Shape: | |
|--|--|
| Round | |
| Thread Class: | |
| 2b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.188 inches | |
| Tempurature Rating: | |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| Between 0.500 inches and 0.562 inches | |
| Connection Style: | |
| Swivel nut flare 1st end | |
| End Connection Design: | |
| Straight 2nd end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Thready Qty Per Inch (tpi): | |
| 27 2nd end | |
| Burst Test Pressure: | |
| 700.0 pounds per square inch | |
| Layer Composition And Location: | |
| 1st layer braided cotton cord and 2nd layer braided cotton cord and outer layer molded rubber, | |
| Thread Size: | |
| 0.438 inches 1st end | |
| Seat Angle: | |
| 37.0 degrees 1st end | |
| Outer Covering Environmental Protection: | |
| Oil resistant and ozone resistant | |
| Vacuum In Torr: | |
| 254.0 | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 6.500 inches | |
| Media For Which Designed: | |
| Fuel/oil, hydrocarbon single response | |
| Thread Series Designator: | |
| Unf 1st end | |
| Shelf Life: | |
| N/a | |
| | |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0