NSN 4720-00-595-1083

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-595-1083

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.687 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel, plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
20000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber,
chloroprene
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and ozone resistant and mildew resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
180.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npt 1st end
Specification Data:
81349-mil-h-13531/mo government specification

2 type and a class

Specification Or Standard:

NSN 4720-00-595-1083

Nonmetallic Hose Assembly - Page 2 of 2



		fe	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0