NSN 4720-00-595-1996

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-595-1996 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.219 inches **Outside Diameter:** 0.438 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 6000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Outer Covering Environmental Protection:** Abrasion resistant and corrosion resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 9.500 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end Shelf Life: N/a

Unit Of Measure:

NSN 4720-00-595-1996

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0