

View Online at <https://aerobasegroup.com/nsn/4720-00-595-2366>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response

Outside Diameter:

1.234 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

14 1st end

Burst Test Pressure:

3200.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord and 2nd layer molded rubber, composition and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

800.0 pounds per square inch

Thread Size:

1.000 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Fire retardant and fuel resistant and oil resistant and water resistant and ethylene glycol resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

50.500 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0