NSN 4720-00-595-2387

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-595-2387

| 3b 1st end |
|---|
| Thread Direction: |
| Right-hand 1st end |
| Tempurature Rating: |
| -69.0 degrees fahrenheit and 160.0 degrees fahrenheit single response |
| Outside Diameter: |
| Between 0.391 inches and 0.485 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Burst Test Pressure: |
| 1250.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided cotton cord and outer layer molded rubber |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 400.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Abrasion resistant and fuel resistant and oil resistant |
| Vacuum In Torr: |
| 254.0 |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 12.500 inches working |
| Thread Series Designator: |
| Unf 1st end |
| Specification Data: |
| 88044-an6270 government standard |

NSN 4720-00-595-2387

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0