NSN 4720-00-595-2388

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-595-2388

Cross Sectional Shape:
Round
Thread Class:
2b and 2a 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.125 inches
Exterior Color:
Black
Connection Style:
Inverted flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal and external tube 2nd end
Thready Qty Per Inch (tpi):
24 2nd end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided cotton cord and outer layer molded rubber, synthetic
Thread Size:
0.438 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
1500.0 pounds per square inch
Outer Covering Environmental Protection:
Weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.094 inches and 14.344 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Uns and unf 2nd end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-00-595-2388

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0