

View Online at <https://aerobasegroup.com/nsn/4720-00-595-2437>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.234 inches and 0.266 inches

Temperature Rating:

-69.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

Outside Diameter:

Between 0.453 inches and 0.500 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

1250.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and outer layer molded rubber

Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

400.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and fuel resistant and oil resistant

Vacuum In Torr:

254.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

32.000 inches working

Thread Series Designator:

Unf 1st end

Specification Data:

88044-an6270 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0