NSN 4720-00-595-4290

Unf 2nd end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-595-4290

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.344 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.547 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
18.500 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

NSN 4720-00-595-4290

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0