Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-595-4306

Cross Sec	tional Shape:
Round	
Thread Cl	ass:
2b 1st end	
Thread Di	rection:
Right-hand	1 1st end
Inside Dia	meter:
0.437 inch	es
Tempurat	ure Rating:
-65.0 degr	ees fahrenheit and 200.0 degrees fahrenheit single response
Outside D	iameter:
0.843 inch	es
Connectio	on Style:
Swivel nut	flare 1st end
End Conn	ection Design:
Straight 1s	t end
Connectio	on Type:
Threaded i	internal tube 1st end
Burst Tes	t Pressure:
16000.0 po	bunds per square inch
Layer Cor	nposition And Location:
1st layer b	raided steel wire and 2nd layer braided cotton cord and outer layer molded rubber, synthetic
Maximum	Operating Pressure:
3000.0 pot	unds per square inch
Thread Siz	ze:
0.750 inch	es 1st end
Seat Angl	e:
37.0 degre	es 1st end
Outer Cov	ering Environmental Protection:
Abrasion r	esistant and mildew resistant
Inside Su	face Condition:
Smooth	
Measuring	g Method And Length:
19.000 inc	hes working
Media For	Which Designed:
Alcohol, e	thyl and hydraulic fluid single response
Thread Se	ries Designator:
Unf 1st en	d
Shelf Life:	
N/a	
Unit Of M	easure:

## NSN 4720-00-595-4306

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

