NSN 4720-00-595-4332

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-595-4332

Cross Sectional Shape:
Round
Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Inside Diameter:
0.406 inches
Outside Diameter:
0.765 inches
Connection Style:
Swivel nut flare all ends
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting aluminum alloy all ends
Connection Type:
Threaded internal tube all ends
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided steel wire and 3rd layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees all ends
Outer Covering Environmental Protection:
Fuel resistant and corrosion resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
40.000 inches working
Media For Which Designed:
Hydraulic fluid, phosphate-ester base 1st response
Thread Series Designator:
Unf 1st end
Specification Data:
96906-ms28741 government standard
Shelf Life:

N/a

NSN 4720-00-595-4332

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0