NSN 4720-00-595-4736

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-595-4736

Right-hand 1st end
Inside Diameter:
0.438 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
0.641 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
16 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end

NSN 4720-00-595-4736

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0