## NSN 4720-00-598-4356

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-598-4356

Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
4.625 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.875 inches 2nd end
0.875 inches 2nd end Seat Angle:
Seat Angle:
Seat Angle: 12.0 degrees 1st end
Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure:
Seat Angle: 12.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch
Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle:
Seat Angle: 12.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Flow Angle: 90.0 degrees 2nd end
Seat Angle: 12.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Flow Angle: 90.0 degrees 2nd end  Outer Covering Environmental Protection:
Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant
Seat Angle: 12.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Flow Angle: 90.0 degrees 2nd end  Outer Covering Environmental Protection:  Corrosion resistant  Vacuum In Torr:
Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8
Seat Angle: 12.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Flow Angle: 90.0 degrees 2nd end  Outer Covering Environmental Protection:  Corrosion resistant  Vacuum In Torr: 50.8  Inside Surface Condition:
Seat Angle: 12.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Flow Angle: 90.0 degrees 2nd end  Outer Covering Environmental Protection: Corrosion resistant  Vacuum In Torr: 50.8  Inside Surface Condition: Smooth
Seat Angle: 12.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Flow Angle: 90.0 degrees 2nd end  Outer Covering Environmental Protection:  Corrosion resistant  Vacuum In Torr: 50.8  Inside Surface Condition:  Smooth  Measuring Method And Length:

## NSN 4720-00-598-4356

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

Chafe guard

**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A542a0