## NSN 4720-00-600-9020

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-600-9020

| Cross Sectional Shape:   |
|--|
| Round  |
| Inside Diameter:   |
| Between 0.305 inches and 0.336 inches  |
| Tempurature Rating:  |
| -65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response  |
| Outside Diameter:  |
| Between 0.547 inches and 0.637 inches  |
| Minimum Inside Bending Radius:   |
| 2.750 inches   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Unthreaded external tube 1st end   |
| Burst Test Pressure:   |
| 4000.0 pounds per square inch  |
| Layer Composition And Location:  |
| 1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric |
| Maximum Operating Pressure:  |
| 1000.0 pounds per square inch  |
| Hydrostatic Test Pressure:   |
| 2000.0 pounds per square inch  |
| Outer Covering Environmental Protection:   |
| Fuel resistant and oil resistant and water resistant   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 23.500 inches and 24.500 inches  |
| Outside Diameter Tube Accommodated:  |
| 0.372 inches 1st end   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A542a0   |
|  |