

View Online at <https://aerobasegroup.com/nsn/4720-00-600-9033>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

Between 0.305 inches and 0.336 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.547 inches and 0.637 inches

**Minimum Inside Bending Radius:**

2.750 inches

**End Connection Design:**

Straight 1st end

**Connection Type:**

Unthreaded external tube 1st end

**Burst Test Pressure:**

4000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Hydrostatic Test Pressure:**

2000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and oil resistant and water resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

46.500 inches and 47.500 inches

**Outside Diameter Tube Accommodated:**

0.372 inches 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0