## NSN 4720-00-600-9033

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-600-9033

Cross Sectional Shape:
Round
Inside Diameter:
Between 0.305 inches and 0.336 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
Between 0.547 inches and 0.637 inches
Minimum Inside Bending Radius:
2.750 inches
End Connection Design:
Straight 1st end
Connection Type:
Unthreaded external tube 1st end
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
1000.0 pounds per square inch
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and water resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
46.500 inches and 47.500 inches
Outside Diameter Tube Accommodated:
0.372 inches 1st end
Shelf Life:
N/a
Unit Of Measure:
<u></u>
Demilitarization:
No
Fiig:
A542a0