## NSN 4720-00-600-9153

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-600-9153

Cross Costional Change
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.687 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
20000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
51.000 inches
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Nptf 1st end
Shelf Life:

N/a

## NSN 4720-00-600-9153

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0