NSN 4720-00-602-5988

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-602-5988 **Cross Sectional Shape:** Round **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.422 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response **Outside Diameter:** 0.815 inches **Minimum Inside Bending Radius:** 8.000 inches **Connection Style:** External seat for gasket seal (boss) 1st end **End Connection Design:** Straight 1st end **End Fitting Component And Material:** Socket steel comp 304 2nd end **Fitting Component And Surface Treatment:** Socket cadmium 2nd end **Connection Type:** Threaded external boss 1st end Thready Qty Per Inch (tpi): 12 1st end Second End Relationship With First End: Identical First End Swivel Action Capability: Not included **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 5000.0 pounds per square inch **Thread Size:**

1.750 inches 1st end

Outer Covering Environmental Protection:

Corrosion resistant

Criticality Code Justification:

Zzzy

Inside Surface Condition:

Smooth

NSN 4720-00-602-5988

Nonmetallic Hose Assembly - Page 2 of 2



24.000 inches

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene; packed in a heat sealed polyethylene tube

Thread Series Designator:

Un 1st end

Reference Number Differentiating Characteristics:

Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0