NSN 4720-00-603-1495

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-603-1495

Cross Sectional Shape:				
Round				
Thread Class:				
2b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.875 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response				
Outside Diameter:				
1.200 inches				
Minimum Inside Bending Radius:				
7.380 inches				
Exterior Color:				
Black				
End Application:				
Clark model 290m; tractor, wheeled, ind., diesel driven; med dbp, nsn 2420000889384, w/rops nsn 2420010590090				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 2nd end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
14 1st end				
Burst Test Pressure:				
1500.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided fabric and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric				
Maximum Operating Pressure:				
250.0 pounds per square inch				
Thread Size:				
0.750 inches 2nd end				
Seat Angle:				
37.0 degrees 2nd end				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
23.500 inches				
Media For Which Designed:				

Fuel/oil, hydrocarbon single response

NSN 4720-00-603-1495

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
1	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	D C3	igilatoi.

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0