NSN 4720-00-604-4409

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-604-4409

0.312 inches			
Tempurature Rating:			
450.0 degrees fahrenheit single response			
Outside Diameter:			
Between 0.430 inches and 0.469 inches			
Minimum Inside Bending Radius:			
4.000 inches			
Exterior Color:			
Natural			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Nuts drilled for lockwire			
Burst Test Pressure:			
9000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
2250.0 pounds per square inch			
Thread Size:			
0.562 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Hydrostatic Test Pressure:			
4500.0 pounds per square inch			
Outer Covering Environmental Protection:			
Corrosion resistant			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
18.000 inches and 18.500 inches			

NSN 4720-00-604-4409

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	ator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0