

View Online at <https://aerobasegroup.com/nsn/4720-00-604-9143>

**Cross Sectional Shape:**

Round

**Thread Class:**

3a 2nd end

**Thread Direction:**

Right-hand 2nd end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.688 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Connection Style:**

Swivel, external seat for gasket seal 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded external tube 1st end

**Thready Qty Per Inch (tpi):**

14 1st end

**Burst Test Pressure:**

20000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

5000.0 pounds per square inch

**Thread Size:**

1.125 inches 2nd end

**Hydrostatic Test Pressure:**

10000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

48.000 inches excluding end fittings

**Seat Radius:**

0.312 inches 1st end

**Special Features:**

P/n 249710-4 ferrule silver brazed to p/n 151945-1 nut

**Media For Which Designed:**

Air and fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Uns 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0