NSN 4720-00-606-5197

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-606-5197

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
1.125 inches
Minimum Inside Bending Radius:
9.000 inches
Exterior Color:
Natural
Connection Style:
Plain optional end 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal pipe 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
1.000 inches 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant
Vacuum In Torr:
304.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
120.000 inches excluding end fittings
Special Features:

Furnished with a strainer and strainer guard

NSN 4720-00-606-5197

Nonmetallic Hose Assembly - Page 2 of 2



M	edia	For	Wh	ich	Des	ian	ed:
יועו	cuia	1 01	***		DEG	ичн	cu.

Air and alcohol, ethyl and fuel/oil, hydrocarbon and water single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0