## NSN 4720-00-606-7293

**Cross Sectional Shape:** 

Round

Smooth

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-606-7293

Inside Diameter:		
0.500 inches		
Tempurature Rating:		
-65.0 degrees fahrenheit single response and 350.0 degrees fahrenheit single response		
Outside Diameter:		
0.655 inches		
Minimum Inside Bending Radius:		
9.000 inches		
Exterior Color:		
Natural		
Angle Between Rigid Elbow Fittings In Deg:		
0.0		
Connection Style:		
Swivel nut flare 2nd end		
End Connection Design:		
Elbow 2nd end		
Connection Type:		
Threaded internal tube 1st end		
Burst Test Pressure:		
6000.0 pounds per square inch		
Layer Composition And Location:		
Outer layer braided corrosion resistant steel wire		
Maximum Operating Pressure:		
1500.0 pounds per square inch		
Thread Size:		
0.875 inches 2nd end		
Seat Angle:		
37.0 degrees 2nd end		
Hydrostatic Test Pressure:		
3000.0 pounds per square inch		
Flow Angle:		
90.0 degrees 2nd end		
Outer Covering Environmental Protection:		
Corrosion resistant		
Inside Surface Condition:		

## NSN 4720-00-606-7293

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Me	thod And	Length:
60.375 inches	working	

**Thread Series Designator:** 

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0