

View Online at <https://aerobasegroup.com/nsn/4720-00-606-9483>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.187 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.359 inches and 0.391 inches

**Connection Style:**

Swivel nut, inverted flare 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded external tube 2nd end

**Thready Qty Per Inch (tpi):**

24 2nd end

**Burst Test Pressure:**

1700.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided cotton cord and outer layer rubber impregnated braided rayon cord

**Maximum Operating Pressure:**

425.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

84.0 degrees 2nd end

**Hydrostatic Test Pressure:**

850.0 pounds per square inch

**Outer Covering Environmental Protection:**

Oil resistant and fuel resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

17.000 inches

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Uns 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0